



Model	Technical name		Technical parameters
VE215N	Flow Rate	50Hz	1.5 CFM
			42 l/min
		60Hz	1.8 0CFM
			50 l/min
	Ultimate vacuum	Partial Pressure	2X10 ⁻¹ Pa
		Total pressure	15micron
	Power		1/4 HP
	Inlet port		1/4" Flare
	Oil Capacity		200 ml
	Dimensions(mm)		308X124X230
Weight		7.5 kg	



Model	Technical name		Technical parameters
VE225N	Flow Rate	50Hz	2.5 CFM
			70 l/min
		60Hz	3.0 CFM
			84 l/min
	Ultimate vacuum	Partial Pressure	2X10 ⁻¹ Pa
		Total pressure	15micron
	Power		1/3 HP
	Inlet port		1/4" Flare
	Oil Capacity		250 ml
	Dimensions(mm)		315X124X240
Weight		8.6 kg	



Model	Technical name		Technical parameters
VE260N	Flow Rate	50Hz	6.0 CFM 170 l/min
		60Hz	7.0 CFM 198 l/min
	Ultimate vacuum	Partial Pressure	2X10 ⁻¹ Pa
		Total pressure	15micron
	Power		3/4 HP
	Inlet port		1/4" & 3/8" Flare
	Oil Capacity		700 ml
	Dimensions(mm)		400X145X270
	Weight		16.5 kg



Loading zoom

Model	Technical name		Technical parameters
VE280N	Flow Rate	50Hz	8.0 CFM
			226 l/min
		60Hz	9.0 CFM
			254 l/min
	Ultimate vacuum	Partial Pressure	2X10 ⁻¹ Pa
		Total pressure	15micron
	Power		1 HP
	Inlet port		1/4" & 3/8" Flare
	Oil Capacity		590 ml
	Dimensions(mm)		400X145X270
Weight		16.7 kg	